

CONWAY P 100 NHC

CONTACTLESS – PEDAL OPERATED BASED



TECHNICAL SPECIFICATION	
MODEL : CONWAY – P 100 NHC – Pedal Operated	
Operating Method	Pedal Type
Flow Rate - (Liters / Hour)	100 LPH
Storage Tank - Normal Water	20 Liters
Storage Tank - Cold Water	20 Liters
Storage Tank - Hot Water	4 Liters
No. of Faucets	3
Net Weight in Kg (Approx.)	56
Purification Method	UV + OZONE
Number of Power Cord	15 Amps 1 number.
Heater Power in Watts	1000 watts
Power Supply (AC 50 Hz)	180 to 260 Volts
MOC - Housing SS 304	Stainless Steel - 0.8 mm Sheet
MOC - Normal Water Tank	LLDPE
MOC – Hot & Cold Water Tank SS 304	Stainless Steel - 0.8 mm Sheet
MOC – Rear cover SS 202	Stainless Steel - 0.8 mm Sheet
MOC - Legs SS 202	Stainless Steel - 2.0 mm Sheet
MOC – Faucets	Brass - Chromium Plated
Insulation of Cooling Tank	Poly Urethane foam
Compressor Make	Emerson
Compressor Refrigerant	R – 134a
Dimension of CONWAY 100	L 455 x W 450 x H 1370 mm
Filtration Technique	Spun Candle and Carbon Block.

